

1. A method for making carbon fibers, the method including the steps of:
providing a precursor fiber;

stabilizing the precursor fiber by heating the precursor fiber in an oxidizing environment in a heating chamber of the furnace while applying tension to the precursor fiber;

carbonizing the stabilized fiber by further heating the fiber in an oxidizing

2. The method of claim 1 in which the steps of stabilizing and carbonizing

continuously introducing ambient air into the furnace;

heating the air; and

blowing the heated air over the fiber in the heating chamber of the furnace.

\3. The method of claim 1 in which the step of stabilizing includes:

initially heating the precursor fiber until reaching a heating chamber

holding the heating chamber at this temperature for approximately 5 minutes

after the precursor material begins to stabilize, raising the heating chamber temperature approximately 1.7-2.8 degrees Celsius per minute to approximately 204

gradually raising the heating chamber temperature to approximately 227 to 250 degrees Celsius by increasing the temperature of the heated air being blown into the heating chamber at a rate sufficient for stabilization but insufficient for

the step of carbonizing includes:

quickly raising the heating chamber temperature to approximately 399 degrees Celsius by increasing the temperature of the air being introduced into the heating chamber at a rate that will carbonize the fiber.

5 4. The method of claim 1 in which the step of carbonizing includes carbonizing the fibers such that each resulting fiber is a biregional fiber that includes an inner non-carbonized core and an exterior carbonized sheath.

5. The method of claim 4 in which the step of providing precursor fibers
10 includes providing a homogeneous polymeric material;

the step of stabilizing includes oxygen stabilizing an outer fiber portion of the polymeric material; and

the step of carbonizing includes forming a carbonized outer region and a non-carbonized inner region of each fiber.

15

6. The method of claim 5 in which the step of providing a homogeneous polymeric material includes providing a standard acrylic polymer.

7. The method of claim 1 in which the step of providing a precursor fiber
20 includes providing a polyacrylonitrile (PAN) fiber.

8. A method for making carbon fibers, the method including the steps of:
providing a precursor fiber;
providing a furnace configured to heat the fiber;
25 stabilizing and carbonizing the fiber in a single continuous process that includes drawing the fiber continuously through the furnace.

9. A method for making carbon fibers, the method including the steps of:
providing an elongated precursor fiber;
30 providing a plurality of furnaces disposed adjacent one another in a serial side-by-side relationship and configured to heat the fiber to different respective temperatures as the fiber is drawn through the furnaces;

09780303 120501

Sub 92

stabilizing the precursor fiber by heating the precursor fiber in an oxidizing environment as it is drawn through respective heating chambers of an initial group of the plurality of furnaces while applying tension to the precursor fiber; and

continuously carbonizing the stabilized fiber by further heating the fiber in an oxidizing environment as it is drawn through the heating chamber of a final one of the plurality of furnaces.

10. The method of claim 9 in which the step of stabilizing the precursor fiber includes:

10 heating the heating chamber of a first one of the plurality of furnaces to a first temperature;

heating the heating chamber of each subsequent furnace to a temperature higher than each respective preceding furnace;

15 heating the heating chamber of one of the furnaces to a temperature just below the flash point of the precursor fiber being stabilized; and

drawing the fiber through the heating chambers of the furnaces starting with the heating chamber of the first furnace.

11. The method of claim 10 in which the step of providing a plurality of furnaces includes configuring the furnaces such that the fiber is exposed to a temperature just below the flash point of the fiber for a longer period of time than the fiber spends at the other temperatures.

12. The method of claim 11 in which the step of providing a plurality of furnaces includes:

providing an additional furnace adjacent the furnace that is heated to a temperature just below the flash point of the precursor fiber being stabilized;

heating the additional furnace to a temperature just below the flash point of the precursor fiber being stabilized; and

30 drawing the fiber through the furnaces such that the fiber passes through the heating chamber of the additional furnace after leaving the heating chamber of the furnace that is heated to just below the flash point of the fiber.

09780303 0209001

B

heating the heating chamber of a final one of the furnaces to a temperature that will carbonize at least a portion of the fiber; and

drawing the fiber through the heating chamber of the final furnace.

the step of stabilizing the precursor fiber includes:

heating the heating chamber of the first furnace to approximately 185 degrees Celsius;

heating the heating chamber of the second furnace to approximately 193 degrees Celsius;

heating the heating chamber of the third furnace to approximately 204 degrees Celsius;

heating the heating chamber of the fourth furnace to approximately 216 degrees Celsius;

heating the heating chambers of the fifth and sixth furnaces to approximately 232 degrees Celsius; and

drawing the fiber through the heating chambers of the first, second, third, fourth, fifth, sixth, and seventh furnaces in sequence.

15. The method of claim 14 in which the step of carbonizing the fiber includes:

heating the heating chamber of the seventh furnace to approximately 260 degrees Celsius; and

drawing the fiber through the heating chamber of the seventh furnace.

16. The method of claim 14 including the additional step of drawing the fiber
30 through the furnace heating chambers at a rate that provides a residence time in each
furnace of approximately 0.6 minutes.

17. The method of claim 15 including the additional step of introducing ambient air into each furnace.

18. The method of claim 17 including the additional step of adjusting
5 downward the amount of ambient air introduced into furnaces that are operating at and above approximately 232 degrees Celsius.

19. The method of claim 18 including the additional step of restricting the
10 airflow in furnaces operating at and above 232 degrees Celsius to approximately 60 percent (by volume) of the airflow in the furnaces operating below 232 degrees Celsius.

20. The method of claim 9 including the additional step of further graphitizing
15 the fiber by adding additional furnaces operating at higher temperatures.

21. The method of claim 9 including the additional step of adjusting fiber draw
rate to optimize the stabilization and carbonization processes.

22. The method of claim 9 in which:
20 the step of providing a plurality of furnaces includes spacing apart at least two adjacent ones of the furnaces; and
including the additional step of exposing the fiber to ambient air between the spaced-apart furnaces.

23. The method of claim 9 in which:
25 the step of providing a plurality of furnaces includes spacing apart at least two adjacent ones of the furnaces; and
including the additional step of enclosing the fiber as it passes between adjacent ones of the furnaces.

30 24. The method of claim 9 including the additional step of controlling the degree of carbonization of the fiber by adjusting the residence time within the furnaces.

009730303 020304
105020 000000

25. The method of claim 9 including the additional step of forming a biregional fiber having an outer carbonized region and an inner virgin material region by carbonizing only an outer portion of the fiber.

5 26. The method of claim 25 in which the step of providing a precursor fiber includes providing a bipolymeric fiber containing an inner core of one polymer and an outer sheath of a second polymer that can be carbonized.

10 27. The method of claim 9 in which the step of providing a precursor fiber includes providing a polyacrylonitrile (PAN) type fiber.

retract
28. An apparatus for forming carbon fibers that includes:
a first furnace having a heater;
an air supply system configured to direct a gas comprising oxygen over the
15 heater and into a heating chamber;
a fiber guide configured to direct a fiber through the heating chamber; and
a dispersion plate disposed between the heater and the heating chamber and
configured to evenly disperse heated air into the heating chamber and around the
fiber.

20

29. The apparatus of claim 28 further including a plurality of fiber guides configured to simultaneously direct a corresponding plurality of fibers through the heating chamber and in which the dispersion plate is configured to evenly disperse heated air over the plurality of fibers.

25

30. An apparatus for forming carbon fibers that includes:

a first furnace having a heater and an air supply system configured to direct a gas comprising oxygen over the heater and into a first heating chamber at a first temperature;

30 a second furnace disposed adjacent the first furnace and having a heater and an air supply system configured to direct a gas comprising oxygen over the heater and into a second heating chamber at a second temperature; and

1. **Introduction**
 2. **Background**
 3. **Methodology**
 4. **Results**
 5. **Discussion**
 6. **Conclusion**
 7. **References**
 8. **Appendix**
 9. **Figure 1**
 10. **Figure 2**
 11. **Figure 3**
 12. **Figure 4**
 13. **Figure 5**
 14. **Figure 6**
 15. **Figure 7**
 16. **Figure 8**
 17. **Figure 9**
 18. **Figure 10**
 19. **Figure 11**
 20. **Figure 12**
 21. **Figure 13**
 22. **Figure 14**
 23. **Figure 15**
 24. **Figure 16**
 25. **Figure 17**
 26. **Figure 18**
 27. **Figure 19**
 28. **Figure 20**
 29. **Figure 21**
 30. **Figure 22**
 31. **Figure 23**
 32. **Figure 24**
 33. **Figure 25**
 34. **Figure 26**
 35. **Figure 27**
 36. **Figure 28**
 37. **Figure 29**
 38. **Figure 30**
 39. **Figure 31**
 40. **Figure 32**
 41. **Figure 33**
 42. **Figure 34**
 43. **Figure 35**
 44. **Figure 36**
 45. **Figure 37**
 46. **Figure 38**
 47. **Figure 39**
 48. **Figure 40**
 49. **Figure 41**
 50. **Figure 42**
 51. **Figure 43**
 52. **Figure 44**
 53. **Figure 45**
 54. **Figure 46**
 55. **Figure 47**
 56. **Figure 48**
 57. **Figure 49**
 58. **Figure 50**
 59. **Figure 51**
 60. **Figure 52**
 61. **Figure 53**
 62. **Figure 54**
 63. **Figure 55**
 64. **Figure 56**
 65. **Figure 57**
 66. **Figure 58**
 67. **Figure 59**
 68. **Figure 60**
 69. **Figure 61**
 70. **Figure 62**
 71. **Figure 63**
 72. **Figure 64**
 73. **Figure 65**
 74. **Figure 66**
 75. **Figure 67**
 76. **Figure 68**
 77. **Figure 69**
 78. **Figure 70**
 79. **Figure 71**
 80. **Figure 72**
 81. **Figure 73**
 82. **Figure 74**
 83. **Figure 75**
 84. **Figure 76**
 85. **Figure 77**
 86. **Figure 78**
 87. **Figure 79**
 88. **Figure 80**
 89. **Figure 81**
 90. **Figure 82**
 91. **Figure 83**
 92. **Figure 84**
 93. **Figure 85**
 94. **Figure 86**
 95. **Figure 87**
 96. **Figure 88**
 97. **Figure 89**
 98. **Figure 90**
 99. **Figure 91**
 100. **Figure 92**
 101. **Figure 93**
 102. **Figure 94**
 103. **Figure 95**
 104. **Figure 96**
 105. **Figure 97**
 106. **Figure 98**
 107. **Figure 99**
 108. **Figure 100**
 109. **Figure 101**
 110. **Figure 102**
 111. **Figure 103**
 112. **Figure 104**
 113. **Figure 105**
 114. **Figure 106**
 115. **Figure 107**
 116. **Figure 108**
 117. **Figure 109**
 118. **Figure 110**
 119. **Figure 111**
 120. **Figure 112**
 121. **Figure 113**
 122. **Figure 114**
 123. **Figure 115**
 124. **Figure 116**
 125. **Figure 117**
 126. **Figure 118**
 127. **Figure 119**
 128. **Figure 120**
 129. **Figure 121**
 130. **Figure 122**
 131. **Figure 123**
 132. **Figure 124**
 133. **Figure 125**
 134. **Figure 126**
 135. **Figure 127**
 136. **Figure 128**
 137. **Figure 129**
 138. **Figure 130**
 139. **Figure 131**
 140. **Figure 132**
 141. **Figure 133**
 142. **Figure 134**
 143. **Figure 135**
 144. **Figure 136**
 145. **Figure 137**
 146. **Figure 138**
 147. **Figure 139**
 148. **Figure 140**
 149. **Figure 141**
 150. **Figure 142**
 151. **Figure 143**
 152. **Figure 144**
 153. **Figure 145**
 154. **Figure 146**
 155. **Figure 147**
 156. **Figure 148**
 157. **Figure 149**
 158. **Figure 150**
 159. **Figure 151**
 160. **Figure 152**
 161. **Figure 153**
 162. **Figure 154**
 163. **Figure 155**
 164. **Figure 156**
 165. **Figure 157**
 166. **Figure 158**
 167. **Figure 159**
 168. **Figure 160**
 169. **Figure 161**
 170. **Figure 162**
 171. **Figure 163**
 172. **Figure 164**
 173. **Figure 165**
 174. **Figure 166**
 175. **Figure 167**
 176. **Figure 168**
 177. **Figure 169**
 178. **Figure 170**
 179. **Figure 171**
 180. **Figure 172**
 181. **Figure 173**
 182. **Figure 174**
 183. **Figure 175**
 184. **Figure 176**
 185. **Figure 177**
 186. **Figure 178**
 187. **Figure 179**
 188. **Figure 180**
 189. **Figure 181**
 190. **Figure 182**
 191. **Figure 183**
 192. **Figure 184**
 193. **Figure 185**
 194. **Figure 186**
 195. **Figure 187**
 196. **Figure 188**
 197. **Figure 189**
 198. **Figure 190**
 199. **Figure 191**
 200. **Figure 192**
 201. **Figure 193**
 202. **Figure 194**
 203. **Figure 195**
 204. **Figure 196**
 205. **Figure 197**
 206. **Figure 198**
 207. **Figure 199**
 208. **Figure 200**
 209. **Figure 201**
 210. **Figure 202**
 211. **Figure 203**
 212. **Figure 204**
 213. **Figure 205**
 214. **Figure 206**
 215. **Figure 207**
 216. **Figure 208**
 217. **Figure 209**

38. The apparatus of claim 30 in which the dispersion plate includes a plurality of symmetrically spaced air passageways configured to evenly disperse the flow of air entering the heating chamber.